



Specifications Multipack 4x Philips LED Downlight Ledinaire DN065B Metal White 19W 2000lm 110D - 830-840-865 CCT | 225mm - Cutout 200mm - IP20

[View Product](#)

## General Information

|                          |  |
|--------------------------|--|
| SKU                      | 253041   |
| EAN                      | 8719157059374  |
| Brand                    | Philips  |
| Manufacturer Name        | Multipack 4x DN065B G4 LED20/830_840_865 19W D200 RD |
| Any Lamp all-in warranty | 3 Years  |
| Average Lifetime (h)     | 30000  |

## Technical Information

|                             |   |
|-----------------------------|---|
| Emergency Lighting          | No Emergency Unit                               |
| Tiltable                    | No  |
| Technology                  | LED Integrated                                  |
| Voltage (V)                 | 220-240   |
| Dimmable                    | Not Dimmable                                    |
| Colour Code                 | 830 Warm White, 840 Cool White, 865 Daylight    |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White, 6500 Daylight |
| Colour Rendering (Ra)       | 80-89   |
| Colour of Light             | White   |
| Light colour options        | CCT   |
| Including bulb              | Yes   |
| Amount of bulbs required    | 1   |

|                          |                                       |
|--------------------------|---------------------------------------|
| Beam Angle (degree)      | 110                                   |
| Luminous Efficacy (lm/W) | 105                                   |
| Power factor             | >0.90                                 |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | Plastic                               |
| Finish of Reflector      | Frosted                               |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 200                    |
| IP-rating              | IP20                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Metal                  |
| Colour of the Fixture  | White                  |
| Fixture Connection     | Screw terminal, 2-pole |
| Series                 | DN065B                 |

## Dimensions

|               |     |
|---------------|-----|
| Diameter (mm) | 225 |
|---------------|-----|

## Sensor Information

## Why Any-lamp?

|   |   |
|---|---|
| Type of sensor  | No Sensor   |
|  Order from the <b>largest lighting specialist</b> in Europe |  <b>Customised</b> quotation |
|  Up to <b>7 years warranty</b>                               |  <b>Easy</b> return process    |